

Optical Fiber Pigtail And Patch Cord



Features

- Low insertion loss
- Ultra low return loss
- Multiple connector types available
- Multiple cable coating (PVC, OFNRLSZH) available

Applications

- Long haul, Metro and Access system
- Fiber CATV
- Fiber data network
- Terminator for active optical modules



Technical parameter

Parameter		Fiber connector		
Operating Wavelength(nm)		Multi-Mode	Single Mode	
Fiber Type		850/1310	1310/1550	980/1060
Insertion Loss		≤0.2	≤0.2	≤0.4
Return Loss	UPC	≥40	≥50	≥50
	APC	/	≥50	≥50
Repeatability(dB)		≤0.1		/
Changeability(dB)		≤0.2		
Durability		≥1000		
Operating Temperature		-40~+85		

Ordering Information

OFC	X-	XX-	XX-	XX	XX-	XX-
	S: Single Mode D: Multi-Mode	SA:SC/APC SC:SC/UPC MU:MU/UPC 00: no connect	SA:SC/APC SC:SC/UPC MU:MU/UPC 00: no connect	09:0.9mm 20:2.0mm 30:3.0mm	0:G652D 1:G657A 2:50/125 3:62.5/125 4:others	0.5:0.5m 1.0:1.5m 10:10m
		Connector Type	Connector Type	Cable Dia.	Fiber Type	Length

